



Unique
resonant
tube
technology

High
accuracy

Simple
operating

Easy
cleaning

PORTABLE / LABORATORY DENSITY METER

IN PROCESS TO EXCELLENCE

Specifications

Density Range	0 to 3 g/cm ³
Density Accuracy	±0.0002 g/cm ³ ±0.0005 g/cm ³ ±0.001 g/cm ³
Temperature Range	0°C to +50°C (+32°F to +122°F)
Temperature Accuracy	±0.1°C (±0.2°F)
Data Handling	Back lighted LCD 4 x 20
Ambient Temperature Range	+10°C to +40°C (+50°F to +104°F)
Weather Rating	IP65
Material	Stainless steel 316L
Power Supply	110-220V AC
Data Transfer	Bluetooth
Viscosity Effect	Automatically compensated
Quality Assurance	ISO 9001:2000
Factory Calibration	Calibration certificates supplied as standard
CE Mark	Compliant EN 61326 ; EN5011 ; EN 50082-2
Housing Dimensions (L x W x H)	140 x 100 x 290 mm (5.5 x 3.9 x 11.4 in)
Weight	approx. 2 kg (approx. 4.4 lb)

Applications

- Products consistency and adulteration check
- Molasses density control in ethanol production
- Chemical, cosmetic, pharmaceutical industries
- Petroleum industry
- Food, milk and dairy products
- % alcohol check in beverages industry
- Density control at outlets and delivery points

Advantages

- Direct density measurement
- Automatic temperature compensation
- Rigorous factory calibration and testing
- Small and compact
- Maintenance free

Principle of operation

The operating principle is resonant method (vibration element) of measurement. It is based on the changing of frequency characteristics of the sensitive unit and resistance of the built-in temperature sensor in dependence of characteristics of the measured liquid.

Resonant tube technology implemented in DM-300 density meter achieve higher accuracy and stability of the measurements.

Design of the device considerably simplifies sampling and sample preparing procedure. Operator doesn't need any plastic syringes and other special laboratory glassware! Measuring chamber is especially designed for very viscous liquids. Cleaning procedure is shortened for more than 2 times comparing to similar class devices!



Data transmission to PC or portable printer via Bluetooth connection

For more information please visit www.lemis-process.com



USA
LEMIS USA, Inc.
 15556 Summit Park Dr. Suite 601
 Montgomery
 TX 77356, USA
 Ph.: +1 281 465 8441

EUROPE
AS LEMIS Baltic
 26 Ganību dambis
 Rīga, LV-1005
 Latvia, EU
 Ph.: +371 6738 3223
 Fax: +371 6738 3270

INDIA
LEMIS India PVT LTD
 504, Bhumiraj Costarica, 5th floor
 Plot 1&2, Sector 18, Sanpada
 Navi Mumbai-400705, INDIA
 Ph.: +91 22 6721 5655
 Fax: +91 22 6794 2666

E-mail: info@lemis-process.com